




DURACOVER Damper Covers



DURACOVER Damper Covers, for use on printing presses with traditional dampening systems, have been developed to provide efficient and consistent dampening. A wide range of sizes and choice of materials enable the printer to select the optimum damper cover for each application.

 <p>HEIDELBERG QM46 #A1.205.026</p>	Code	DFQM46
	L	360.0mm
	W	30.0mm
	Thickness	5.0mm
 <p>HEIDELBERG QM461 #A1.205.511</p>	Code	DFQM461
	L	360.0mm
	W	38.0mm
	Thickness	5.0mm
 <p>HEIDELBERG QM46DI #A1.205.014</p>	Code	DFQM46DI
	L	360.0mm
	W	74.0mm
	Thickness	5.0mm

3C - 83



SYNTHETIC DAMPER COVERS

For use on the Form or Plate rollers. Supplied in rolls. Order according to the diameter of the roller. The following sizes are available:

Roller diameter	Order code	Flat width	Circumference
23 – 34 mm	DCGS23/34	38.1 – 50.8mm	75 – 100mm
34 – 45mm	DCGS34/45	50.8 – 69.8mm	100 – 140mm
45 – 55mm	DCGS45/55	69.8 – 82.5mm	140 – 173mm
54 – 60mm	DCGS54/60	82.5 – 95.2mm	170 – 190mm
59 – 68mm	DCGS59/68	95.2 – 107.9mm	190 – 210mm
68 – 77mm	DCGS68/77	107.9 – 123.8mm	210 – 240mm
76 – 89mm	DCGS76/89	123.8 – 140mm	240 – 280mm
89 – 105mm	DCGS89/105	140 – 160mm	280 – 325mm
105 – 127mm	DCGS105/127	160 -	325 -

QUALITY

- 100% synthetic yarn with shrink fibre
- Shrinks in water to give exact fit without wrinkling
- Easy to fit
- Lint and dust free
- Random loop heights to give consistent dampening leaving no traces on the finished print
- Easy to clean by hand or machine – yarn treated for high ink resistance
- Long lasting with effective dampening throughout the life of the cover

HOW TO FIT

The cover is supplied inside-out for easy fitting:

- Measure length of roller and add enough for limited shrinkage on the roller stocks
- Cut Damper Cover to appropriate length
- Roll cover over roller, leaving sufficient overlap at each end for shrinkage and for fastening at the roller ends
- Do not trim or tie ends before shrinking
- Smooth cover over roller and immerse in warm water (not more than 50°C or 120°F) for 5 minutes or in cold water for 15 minutes. Do not use hot or boiling waters.

DAMPENING FELTS

- Absorbent felt pad for use on Heidelberg press models
- Available for Quickmaster 46 and 46DI

www.pcsman.com